





Improvement of Print Speed Enhanced FINE™ Imaging Technology 300, 600 & 1200dpi Printing Resolution New Input Hopper Removable Output Hopper Support of Transparent Cards Support of CR79 Cards Front-Side Mag Encoding All-in-One type Lock System



IDP's new SOLID-510 is the next generation of its mid-range ID Card Printer platform. The SOLDI-510 inherits the most successful and proven elements of the SOLID-500 series – IDP's longest running ID Card Printer. Enhancements to the SOLID-510 include careful selection of highly reliable parts, the application of a new state-of-the art CPU and application specific features for unique projects.

The new SOLID-510 offers an upgrade path from single side printing (510S), to dual side printing (510D), and to dual side printing with lamination (510L). The SOLID-510L also uses IDP's patented Direct Lamination which is the industry's first adoption of direct lamination technology to drastically reduce heat-up time, save energy, and optimize the application of laminate to the card.

Performance - Essence of Card Printer

The core spirit of a card printer is its print quality, print speed and stability. IDP's new SOLID-510 card printer increases print speeds up to by 10%, enhances print quality by optimizing precise ribbon movement, and provides faster processing speed by utilizing a new powerful CPU.



Careful Consideration of User Convenience

From the initial design of the SOLID-510 Series, IDP has taken careful consideration of the end-user to create an easy to use and flexible card printer. The SOLID-510 offers a larger card loading capacity (up to 200 cards), a choice of output direction, new cartridge $loading\ lamination, support\ of\ transparent\ magnetic\ cards, optional\ support\ of\ CR79\ card$ and an optional all-in-one type lock system are all features of the new SOLID-510.

With a more advanced SOLID-510 from IDP, card issuance will be easier and more productive than ever before.



SOLID Applications ensure proper card issuance and data management with SOLID series printers at no extra cost.

- Design and Print (Images, Photos, Texts, etc.) 1D & 2D Barcode printing
- Auto portrait
- (Auto face detection & adjustment of size & position)
- Card design templates Plug-in for supporting external devices
- Convenient issuance of cards and data management Magnetic stripe (MS), contact & contactless smart card encoding
- by using plug-in program



SOLID series provides effective security features for access control and data encryption.

SOLID series has a password verification function to provide administrator and user authentications.

SOLID series can set a specific authorized PC for encoding and printing cards.

SOLID series can encrypt data transmitted on USB and can support SSL (Secure Socket Layer) protocol on ethernet communications.



SOLID series can utilize the network printer server for encoding and printing cards.

SOLID Ethernet module can not only print cards but also encode MS, contact and contactless smart card through the network.

SOLID Ethernet module has OCP(Open Card Print) protocol which can encode and print cards by using commands on multiple platforms without installing the printer driver.

Available encoding the contact & contactless smart card by Ethernet.



SPECIFICATIONS

PRINTING

Print Type Dye-Sublimation Print Area Edge to Edge

• Resolution 300dpi (Color & Mono), 600 & 1200dpi (Mono only)

• Dual Sided Printing Option (with Flipper)

CARD

Card Feeding Automatic

• Card Size ISO CR80 or ISO CR79 (Option-Factory installed)

Card Thickness
Card Type
O.38mm (15mil), 1.0mm (40mil)
PVC, PET, Composite PVC

PRINT SPEED

Monochrome 5 sec_/card (720 cards/hour)

YMCKO
Front-in & Front-out : Max. 17 sec /card (212 cards/hour)
Front-in & Back-out : Max. 16 sec /card (225 cards/hour)

CAPACITY

• Input Hopper 100 cards / 200 cards with cover open

Output Hopper Front: 40 cards / Back: 100 cards (Optional Back-side Stacker)

SYSTEM

• Memory 64MB RAM

• Display & Button 2 Line LCD / 2 LED Buttons

• Supported Platforms Microsoft Windows 7/ 8/ 10, Mac OS, Linux

• Communication USB, Ethernet (Option)

• Power Free Voltage (AC100/ 240V, 50~60Hz) / 48W

• Temperature/Humidity $15~35\,^{\circ}$ / 35~70%

Security Physical Lock & Kensington Lock (Option)

DIMENSIONS / WEIGHT

Millimeter (WxLxH)
Inch (WxLxH)
6.5 x 390 x 210
f.5 x 15.4 x 8.3
Kg/lbs
Kg/lbs

ENCODING OPTIONS

Magnetic ISO7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II

• Contact ISO 7816 (ID-1)

Contactless
MIFARE, ISO 14443 (Type A/ B), ISO 15693, DESFIRE, iCLASS

CERTIFICATIONS



FEATURES

• New Input Hopper 200 cards with cover open | 100 cards in default



 Removable -Output Hopper





- Front-side Mag Encoding (*Option)
- Support of Transparent Card
- Support CR79 Type (Factory-installed, *Option)

- Improvement of Print speed
- Enhanced FINE™ Imaging Technology
- State-of-the-art CPU
- Reduced Printing Noise
- All-in-one Lock system (*Option)
- Easy to Handle Laminate Film Cartridge

• Rear-side Stacker (up to 100 cards, *Option)



*Print Speed : May change under specific condition.

Specifications and availability may change without notice.

CONSUMABLES

COLOR RIBBONS		
YMCKO	250 Cards/Roll	Full Color Ribbon with Resin Black & Overlay
ҮМСКОК	200 Cards/Roll	Full Color Ribbon with Resin Black, Overlay & Black for Back Side
YMCFKO	200 Cards/Roll	Full Color Ribbon with UV Panel, Resin Black and Overlay
НҮМСКО	350 Cards/Roll	Half Panel Size Color Ribbon with Resin Black and Overlay

SECURITY FILMS		
HPF	250 Cards/Roll	Hologram Patch Film
CPF	250 Cards/Roll	Clear Patch Film

MONO RIBBONS		
ко	600 Cards/Roll	Black with Overlay
К	1200 Cards/Roll	Black
W	1200 Cards/Roll	White
В	1200 Cards/Roll	Blue
R	1200 Cards/Roll	Red
MG	1200 Cards/Roll	Metallic Gold
MS	1200 Cards/Roll	Metallic Sliver
SO	1200 Cards/Roll	Scratch-Off

Authorized Reseller:



FAITH INTERNATIONAL GENERAL TRADING LLC

Plot No. 318-883, Office No. 206, 2nd Floor, Al Safa Business Centre, Street No 19 Karama, Opp. Dubai Central Post office, Post Box No -413373, Dubai (UAE)

8 +971 4 277 0936

infoigt@faithigts.com



